

## ETA Buffer Tank

	SP 825	SP 1000	SP 1100	SP 1650	SP 2200
	SPS 825	SPS 1000	SPS 1100	SPS 1650	SPS 2200
volume (L)	825	1000	1100	1650	2200
Allowable operating pressure (bar)	3	3	3	3	3
Allowable operating temperature (°C)	95	95	95	95	95
Weight without solar coil (kg)	131	150	154	287	328
Diameter w/o insulation (mm)	790	790	85	1000	1115
Diameter w/ insulation (mm)	990	990	1050	1200	1315
H Height (mm)	1939	2199	2150	2370	2360
K Tilt height (mm)	1990	2240	2200	2430	2420
M0 tapping 6/4" (mm)	top	top	top	top	top
M1 tapping 6/4" (mm)	1718	1998	1910	2095	2080
T1 Temperature sensor pocket 1/2" (mm)	1628	1908	1820	2005	1985
T2 Temperature sensor pocket 1/2" (mm)	-	1613	-	-	1755
M2 tapping 6/4" (mm)	1393	1513	1535	1710	1655
T3 Temperature sensor pocket 1/2" (mm)	1083	1413	1240	1310	1555
T4 Temperature sensor pocket 1/2" (mm)	-	1043	-	-	1200
T5 Temperature sensor pocket 1/2" (mm)	833	943	940	1020	1100
M3 tapping 6/4" (mm)	773	883	875	940	965
T7 Temperature sensor pocket 1/2" (mm) (only for SP)	253	253	275	310	325
M4 tapping 6/4" (mm)	148	148	170	205	230
Foam insulation (mm)	100	100	100	100	100
M5 tapping 2" (mm)	-	-	-	-	1970
M6 tapping 2" (mm)	-	-	-	-	360